Piezoelectric Voltage output type (IEPE) accelerometer

General-purpose tri-axial accelerometer　Model：U323E.5

PERFORMANCE	ENGLISH	SI
sensitivity（±10%）	50 mV/g	5.10 mV/(m/s²)
measuring range	±100 g pk	±980 m/s² pk
frequency range(±5%)【2】	1 ~ 8k Hz	1 ~ 8k Hz
frequency range(±10%)【2】	0.5 ~ 9k Hz	0.5 ~ 9k Hz
resonance frequency【1】	>37K	>37K
non-linearity【3】	⩽1%	⩽1%
transverse sensitivity	⩽5%	⩽5%
resolution ratio	0.0002 g rms	0.002 m/s² rms
Environmental character		
overload limit	±2,000 g pk	±19,600 m/s² pk
temperature range	-67～+248 ℉	-55～+120 ℃
Electrical character		
excitation voltage 【4】	+18~+30 VDC	+18~+30 VDC
excitation current【5】	2~20 mA	2~20 mA
bias voltage【1】	11V±1.5V	11V±1.5V
electrical isolation	-	-
output polarity【1】	positive	positive
physical character		
sensing geometry	ceramic	ceramic
structure mode	shear	shear
housing material	Titanium	Titanium
sealing mode	laser welding	laser welding
dimension	0.59×0.59×0.41 in	15×15×10.5 mm
weight【1】	0.43 oz	12.2 g
electrical connector	1/4-28 4-pin	1/4-28 4-pin
electrical connection location	-	-
mounting	Adhesive/10-32 UNF	Adhesive/10-32 UNF

TYPICAL FREQUENCY RESPONSE：





NOTE：

［1］ Inherent characteristics

［2］ The low frequency response is determined by the external signal conditioner

［3］ least square method

［4］ two-wire constant current incentive source power supply,recommened 24V.

［5］ excitation current recommened 4mA.

DRAWING：